

Recessed luminaire. Housing and diffuser frame of painted sheet steel with lateral openings for light emission; for recessed ceilings or ceilings with visible T-rails 24mm or 15mm; Housing colour traffic white RAL 9016. Direct/indirect distribution. Homogeneous illumination by satinised special acrylic panel, with high transmission. Electrical connection via five-pole connection terminal with plug-in contacts; with integrated protective earth conductor connection and release button, suitable for rigid and flexible conductors up to 2.5mm<sup>2</sup>.



- Article No.: 5426116680
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct distribution
- Type of installation: Ceiling installation individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 600 x 600 x 138 (mm)
- Ceiling system: Ceilings with visible T-rails [s-TS] (600x600 mm), cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 578 x 578 (mm)
- Ceiling thickness min/max: 5 / 20 (mm)
- Module axis LxW: 600 x 600 (mm)
- Installation depth: 120(AD); 120(s-TS) (mm)
- Weight (net): 3.616 (kg)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 99 % / 1 %
- UGR lat/lon: 22.3 / 22.2
- Luminaire luminous flux: 5000 (lm)
- LED service life: 50000h L80/B10 (Tq 25°C)
- Luminaire luminous efficacy: 117 (lm/W)
- System output: 40 (W)
- Controller: Electronic driver DALI (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class/light source: B