


Recessed downlight. Housing made of sheet steel with cover ring made of painted pressure-cast aluminium. With translucent cover made of safety glass IP54. Including mounting springs for installation without tools, suitable for ceiling thicknesses 10-25mm. Housing colour grit grey metallic. Direct wide distribution. Light distribution via micro-structured, individually anodised reflector of ultrapure aluminium. Toolless reflector assembly via snap in spring system. External supply unit wired with luminaire ready for operation. Electrical connection via three-pole terminal with plug-in contact.




- Article No.: 8791314125
- Housing material: steel
- Housing colour: grit grey metallic
- Light distribution: direct wide distribution.
- Type of installation: Individual recessed mounting
- Certification mark: IP 54, Protection class II, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 246 x 113 (mm)
- External driver housing LxWxH: 167 x 146 x 48 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 229 (mm)
- Ceiling thickness min/max: 10 / 25 (mm)
- Installation depth: 165(AD) (mm)
- Weight (net): 0.93 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 20.6 / 20.6
- Luminaire luminous flux: 1100 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 118 (lm/W)
- System output: 10 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: D