


Surface-mounted luminaire. Round aluminium profile, texture painted. Suitable for ceiling and wall mounting. Housing colour traffic white RAL 9016. Direct/indirect distribution. Homogenous illumination by satinised special acrylic pane with high transmission. Indirect ratio for a smooth ceiling/wall illumination. Electrical connection via three-pole feed-in and connection terminal with plug-in technology, with integrated protective earth connection and unlocking button, suitable for rigid and flexible cables up to 2,5mm². Easy mounting due to bayonet lock and plug & play connection.




- Article No.: 4676134180
- Housing material: Aluminium
- Housing colour: traffic white RAL 9016
- Light distribution: direct/indirect distribution
- Type of installation: Individual surface mounting
- Certification mark: IP 20, Protection class I, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 600 x 69 (mm)
- Depth: 102 (mm)
- Mounting distance A1: 150 (mm)
- Mounting distance A2: 75 (mm)
- Mounting distance A3: 260 (mm)
- Weight (net): 7.5 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
- Direct/Indirect: 97 % / 3%
- UGR lat/lon: 23.1 / 23.1
- Luminaire luminous flux: 6100 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 133 (lm/W)
- System output: 46 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C