


phase track luminaire. Sheet steel housing, powder-coated. Housing colour traffic white RAL 9016. Direct asymmetrical light distribution. Perfect illumination of vertical illumination surfaces thanks to the luminaire body which can be swiveled up to 60°. Translucent lens optics made of acrylic with additional lateral transmission. Electrical connection via 3-phase conductor rail + universal adapter for ET (switchable). For conductor rail system Lichtwerk DPSN/DPSNA, Global Trac, Eutrac, Iguzzini, Ivela, Reggiani, Targetti. Available accessories: Tool clip-TT ERW to release luminaire from track (722 9000 100)




- Article No.: 7735344100
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct asymmetrical distribution
- Type of installation: Track mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 915 x 55 x 40 (mm)
- Weight (net): 1.6 (kg)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 98 % / 2 %
- UGR lat/lon: 16.8 / 20.0
- Luminaire luminous flux: 3300 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 164 (lm/W)
- System output: 20 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: D