


Spotlight. Compact spotlight unit made of die-cast aluminium with driver integrated into hinged arm. Housing colour silver grey/white aluminium RAL 9006. Direct, narrow-beam distribution. Light distribution using matt, faceted reflector made of highly efficient MIRO-SILVER aluminium with reflection coefficient of 99.8% ; beam angle 30°; clear safety glass. Integrated electronic LED driver. Connection via Global Trac 3-phase track adapter. for busbar systems Lichtwerk DPSN/DPSNA, Global Trac, Eutrac, Iguzzini, Ivela, Reggiani, Targetti. Available accessories: Exchangeable, high-gloss, faceted reflector 40° (3214014140) or high-gloss, segmented 60° (3215014140) reflector.




- Article No.: 3512054135
- Housing material: Aluminium
- Housing colour: silver grey/white aluminium RAL 9006
- Light distribution: direct, narrow distribution
- Type of installation: Track mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 110 x 180 x 254 (mm)
- Weight (net): 1.2 (kg)
- Swivel and turn area (x/y/z): + 90° / 0° / 350°

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 90 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 17.6 / 17.6
- Luminaire luminous flux: 3800 (lm)
- Beam angle: 30°
- LED service life: 050000h L80/B50
- Luminaire luminous efficacy: 108 (lm/W)
- System output: 35 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Driver/Breaker: 11 pieces/B10
19 pieces/C10|31 pieces/C16