


Surface-mounted luminaire. Aluminium profile, natural anodised. Face ends sheet steel, painted white aluminium. Concealed sheet steel rail for ceiling mounting without tools. Housing colour natural anodised aluminium. Direct distribution. White-opal satin-finished polycarbonate extruded profile with white reflectors. Electrical connection via three-pole connection terminal with plug-in contacts; with integrated protective earth conductor connection and release button, suitable for rigid and flexible conductors up to 2.5mm². Available accessories: Suction pad SH 55 for removing the diffuser (903 0055 100)




- Article No.: 4354144180
- Housing material: Aluminium
- Housing colour: natural anodised aluminium
- Light distribution: direct distribution
- Type of installation: Individual surface mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 1143 x 72 x 102 (mm)
- Mounting distance A1: 850 (mm)
- Weight (net): 4.6 (kg)
- Cable entry KE X/Y: 0 (mm) / 0 (mm)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 25.3 / 25.3
- Luminaire luminous flux: 2500 (lm)
- LED service life: 50000h L80/B10 (Tq 25°C)
- Luminaire luminous efficacy: 107 (lm/W)
- System output: 24 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class/light source: C