



Installation channel for individual luminaires. Aluminium profile, natural anodised. For cut-out ceilings. Fixing via swivel bracket or optional wire suspension. Housing colour aluminium, naturally anodised. Direct distribution. Transparent polycarbonate extruded profile with inserted micro-prismatic diffuser and white reflectors. Electrical connection via five-pole connection terminal with plug-in contacts; with integrated protective earth conductor connection and release button, suitable for rigid and flexible conductors up to 2.5mm². Available accessories: Suction pad for removing the diffuser SH 55 (903 0055 100), wire suspension to bare ceiling fino-ETS (135 0080 105)




- Article No.: 1350146650
- Housing material: Aluminium
- Housing colour: aluminium, naturally anodised
- Light distribution: direct distribution
- Type of installation: Individual recessed mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 2854 x 86 x 130 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 2844 x 77 (mm)
- Ceiling thickness min/max: 11 / 30 (mm)
- Installation depth: 135(AD) (mm)
- Weight (net): 9.6 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 19.8 / 21.7
- Luminaire luminous flux: 7200 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 123 (lm/W)
- System output: 59 (W)
- Controller: Electronic driver DALI (2 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C