


Surface-mounted luminaire. Extruded sheet steel trapezoid luminaire body, white polycarbonate end faces, direct distribution, opal diffuser, shock-resistant. Cable entries near centre of luminaire, diffuser fixing by engaging; Housing colour traffic white RAL 9016. Direct diffuse light distribution using diffuser profile made of white-opal acrylic glass, convex with inner longitudinal prisms, snap-fit white end faces made of UV-stabilised polycarbonate. Electrical connection via five-pole connection terminal with plug-in contacts. Available accessories: Suspension set GPA-PS 5x0,75 1700mm (216 9005 100)



- Article No.: 2162216680
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct diffuse distribution.
- Type of installation: Individual surface mounting
- Certification mark: IP 44, Protection class I, F, HACCP DIN 10500/Food/IFS-application-related suitability/BRC, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 1204 x 218 x 80 (mm)
- Mounting distance A1: 900 (mm)
- Mounting distance A3: 454 (mm)
- Weight (net): 2.75 (kg)
- Cable entry KE X/Y: 0 (mm) / 0 (mm)

Lighting/Electrical

- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 95 % / 5 %
- UGR lat/lon: 22.1 / 21.4
- Luminaire luminous flux: 5000 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 140 (lm/W)
- System output: 36 (W)
- Controller: Electronic driver DALI (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C