


Light furniture. Base part with clamping mechanism made of stainless steel. Inner mounting plate for taking up the electrical components made of stainless steel. Cover made of massive frosted acrylic glass with welded edges. Suitable for use in public space. Housing colour galvanised. Modular LED technology with wide beam Individual Lens Optic for a homogeneous appearance. Electrical connection via 5-pole plugin connection terminal; with integrated earth conductor connection and unlocking button, suitable for rigid and flexible cables up to 2.5mm<sup>2</sup>. Protected by internal weatherproof junction box.




- Article No.: 8440014100
- Housing material: StZn
- Housing colour: galvanised
- Light distribution: direct distribution
- Type of installation: Free-standing
- Certification mark: IP 65, CE, VDU 65°<1000, F, Protection class I

## Dimensions



- Dimensions LxWxDxH: 500 x 250 x 720 (mm)
- Mounting distance A1: 300 (mm)
- Mounting distance A2: 160 (mm)
- Weight (net): 28.4 (kg)
- Cable entry KE X/Y: 185 (mm) / 0 (mm)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 61 % / 39 %
- UGR lat/lon: 11.3 / 12.6
- Luminaire luminous flux: 900 (lm)
- Luminaire luminous efficacy: 52 (lm/W)
- System output: 18 (W)
- Controller: Electronic driver
- Mains voltage: 230 V / 50 Hz