


Recessed luminaire. Housing made of painted sheet steel with minimalistic rim, for cut-out ceilings and ceilings with visible T-rails 24mm. Toolless mounting by means of pre-assembled fixing springs. Housing colour traffic white RAL 9016. Direct distribution. Homogeneous illumination by satinised special acrylic pane, with high transmission. Separate pluggable driver unit. Electrical connection via five-pole feed-in and connection terminal with plug-in technology, with integrated protective earth connection and unlocking button, suitable for rigid and flexible cables up to 2,5mm<sup>2</sup>. Available accessories: lopia-EM reinforcing for mineral fibre ceilings 625x625 (368 3200 000), 600x600 (368 3260 000)




- Article No.: 3680146680
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct distribution
- Type of installation: Ceiling installation individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 330 x 330 x 102 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 315 x 315 (mm)
- Ceiling thickness min/max: 10 / 20 (mm)
- Installation depth: 120(AD) (mm)
- Weight (net): 2.4 (kg)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 24.1 / 24.1
- Luminaire luminous flux: 2400 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 107 (lm/W)
- System output: 23 (W)
- Controller: Electronic driver DALI (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz