


Recessed luminaire. Round housing made of painted sheet steel with minimalistic rim, for cut out ceilings. Mounted via clips (included). Housing colour traffic white RAL 9016. Direct distribution. Homogeneous illumination by flush inserted satinised special acrylic pane with high transmission. Separate pluggable driver unit. Electrical connection via five-pole feed-in and connection terminal with plug-in technology, with integrated protective earth connection and unlocking button, suitable for rigid and flexible cables up to 2,5mm². Available accessories: lopia-EM R400 reinforcing for mineral fibre ceilings 625x625 (366 4200 000), 600x600 (366 4260 000)



- Article No.: 3664046680
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct distribution
- Type of installation: Ceiling installation individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 440 x 107 (mm)
- External driver housing LxWxH: 138 x 67 x 30 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 425 (mm)
- Ceiling thickness min/max: 10 / 25 (mm)
- Installation depth: 108(AD) (mm)
- Weight (net): 2.7 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 23.1 / 23.1
- Luminaire luminous flux: 2900 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 139 (lm/W)
- System output: 21 (W)
- Controller: Electronic driver DALI (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C