


Recessed luminaire. Round housing made of painted sheet steel with minimalistic rim, for cut out ceilings. Mounted via wire suspension to bare ceiling (included). Housing colour white aluminium RAL 9006. Direct distribution. Homogeneous illumination by flush inserted satinised special acrylic pane with high transmission. Separate driver unit, plug-in design. Electrical connection via 5-pole connection terminal with plug-in contacts; with integrated protective earth conductor connection and release button, suitable for rigid and flexible conductors up to 2.5mm<sup>2</sup>.




- Article No.: 3669046686
- Housing material: steel
- Housing colour: white aluminium RAL 9006
- Light distribution: direct distribution
- Type of installation: Ceiling installation individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 900 x 147 (mm)
- External driver housing LxWxH: 370 x 105 x 40 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 885 (mm)
- Ceiling thickness min/max: 10 / 25 (mm)
- Installation depth: 200(AD) (mm)
- Weight (net): 13.2 (kg)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 23.0 / 23.0
- Luminaire luminous flux: 12200 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 148 (lm/W)
- System output: 82 (W)
- Controller: Electronic driver DALI (2 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C