


Recessed luminaire. Round housing made of painted sheet steel with minimalistic rim, for cut out ceilings. Mounted via wire suspension to bare ceiling (included). Housing colour traffic white RAL 9016. Direct distribution. Homogeneous illumination by flush inserted satinised special acrylic pane with high transmission. Separate pluggable driver unit. Electrical connection via three-pole feed-in and connection terminal with plug-in technology, with integrated protective earth connection and unlocking button, suitable for rigid and flexible cables up to 2,5mm².




- Article No.: 3669044180
- Housing material: steel
- Housing colour: traffic white RAL 9016
- Light distribution: direct distribution
- Type of installation: Ceiling installation individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 900 x 147 (mm)
- External driver housing LxWxH: 370 x 105 x 40 (mm)
- Ceiling system: cut-out ceilings [AD]
- Ceiling cut-out LxW/D: 885 (mm)
- Ceiling thickness min/max: 10 / 25 (mm)
- Installation depth: 200(AD) (mm)
- Weight (net): 13.1 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 23.0 / 23.0
- Luminaire luminous flux: 12200 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 148 (lm/W)
- System output: 82 (W)
- Controller: Electronic driver (2 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C