


Pendant luminaire. Side parts aluminium profile, natural anodised. Face ends and top of the housing painted sheet steel. Housing colour aluminium, naturally anodised. Direct/indirect distribution. White-opal satin-finished polycarbonate extruded profile. Translucent connection cable pre-mounted. Y-wire suspension with quick-adjust coupling, free height adjustment between 150 and 2000mm.




- Article No.: 6710046685
- Housing material: Aluminium
- Housing colour: aluminium, naturally anodised
- Light distribution: direct/indirect distribution
- Type of installation: Pendant individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 1131 x 62 x 71 (mm)
- Pendant length min/max: 150 / 2000 (mm)
- Mounting distance A1: 1107 (mm)
- Weight (net): 4.2 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 73 % / 27 %
- UGR lat/lon: 23.4 / 23.1
- Luminaire luminous flux: 3500 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 91 (lm/W)
- System output: 39 (W)
- Controller: Electronic driver DALI (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C