


Pendant luminaire. U-shaped aluminum profile, naturally anodized. Face ends sheet steel. Textured paint traffic white (similar to RAL 9016). Housing colour traffic white RAL 9016. Housing colour traffic white RAL 9016. Direkt/indirekt strahlend, getrennt dimmbar. Direkt- und Indirektanteil über weiß-opal satinierten Acryl-Diffusor. Translucent connection cable pre-mounted. Six single wire suspensions with quick-adjust coupling, free height adjustment between 150 and 2000mm.




- Article No.: 5485176681
- Housing material: Aluminium
- Housing colour: traffic white RAL 9016
- Light distribution: direct/indirect distribution
- Type of installation: Pendant individual mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 2021 x 1500 x 106 (mm)
- Pendant length min/max: 150 / 2000 (mm)
- Mounting distance A1: 1440 (mm)
- Mounting distance A2: 585 (mm)
- Mounting distance A3: 1405 (mm)
- Weight (net): 22.2 (kg)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 90$  / 4000K
- Direct/Indirect: 64 % / 36 %
- UGR lat/lon: 22.0 / 23.2
- Luminaire luminous flux: 28400 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 108 (lm/W)
- System output: 264 (W)
- Controller: Electronic driver DALI (7 pcs.)
- Mains voltage max.: 230 V / 50 Hz