


Pendant system luminaire. Aluminium profile incl. LED-unit for indirect share, naturally anodised. Three integrated surface mounted spotlights at the bottom of the housing. Housing colour aluminium, naturally anodised/white aluminium. Direct/indirect distribution. Constant indirect share via white-opal, satin-finished acrylic diffuser throughout all system components. Direct share via three integrated surface mounted spotlights, beam angle 40°. Feed-in and through wiring plug-in system 10A. For system profile serio-HITS LB one wire suspension is in scope of delivery. Available accessories: face-ends with wire suspension incl. connection cord and canopy set serio-HITE LED A/E Set 3x0,75 (5430137105); connection cord serio-AL 3x0,75 (5430037105).




- Article No.: 5433144145
- Housing material: Aluminium, Mix
- Housing colour: aluminium, naturally anodised/white aluminium
- Light distribution: direct/indirect distribution
- Type of installation: Pendant light strip mounting
- Certification mark: IP 20, Protection class I, VDU 65°<1000, F, Indoor, CE

Dimensions



- Dimensions LxWxH/DxH: 845 x 61 x 190 (mm)
- Pendant length min/max: 150 / 2000 (mm)
- Mounting distance A1: 845 (mm)
- Weight (net): 4 (kg)

Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
- Direct/Indirect: 50 % / 50 %
- UGR lat/lon: 5.1 / 5.1
- Luminaire luminous flux: 3300 (lm)
- LED service life: 050000h L80/B10
- Luminaire luminous efficacy: 106 (lm/W)
- System output: 31 (W)
- Controller: Electronic driver (2 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C