


Wall system luminaire. Aluminium profile, naturally anodised. Housing colour black RAL 9005. Direct/indirect distribution. Direct asymmetric light distribution via Fresnel lens made from acrylic. Indirect share via white-opal, satin-finished endless diffusor serio-G. Electrical connection via five-pole feed-in and connection terminal with plug-in technology; with integrated protective earth connection and unlocking button, suitable for rigid and flexible cables up to 2,5mm<sup>2</sup>. 5-pole through wiring plugin system 10A. Mounting system to compensate uneven surfaces (1-15mm). Face ends serio-WITE A/E LB and endless diffusor serio-G for indirect share, must be ordered separately according to total system length. Available accessories: Face-end Set serio-WITE LED A/E sw (4430107104); endless diffusor 6m serio-G/06000 LED (5430600180); 10m serio-G/10000 LED (5431000180); 20m serio-G/20000 LED (5432000180).




- Article No.: 4433044104
- Housing material: Aluminium
- Housing colour: black RAL 9005
- Light distribution: direct asymmetric distribution/ indirect symmetric distribution
- Type of installation: Wall light run installation
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 845 x 61 x 106 (mm)
- Depth: 86 (mm)
- Mounting distance A1: 610 (mm)
- Mounting distance A2: 235 (mm)
- Weight (net): 4.3 (kg)
- Cable entry KE X/Y: 377 (mm) / 19 (mm)

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 80$  / 4000K
- Direct/Indirect: 45 % / 55 %
- Luminaire luminous flux: 2400 (lm)
- LED service life: 50000h L80/B10 (Tq 25°C)
- Luminaire luminous efficacy: 124 (lm/W)
- System output: 19 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz
- Energy efficiency class: C