


Spotlight. Compact spotlight unit made of painted die-cast aluminium with thermal separated technology housing. Housing colour traffic white RAL 9016. Direct narrow light distribution. Light distribution using matt segmented reflector made of highly efficient MIRO-SILVER aluminium with reflection coefficient of 99.8%; Beam angle 36°; clear safety glass; Integrated electronic LED driver; connection via universal 3-phase track adapter. Can be turned 350° and swiveled 90°. For conductor rail system Lichtwerk DPSN/DPSNA, Global Trac, Eutrac, Iguzzini, Ivela, Reggiani, Targetti.




- Article No.: 3591024130
- Housing material: Aluminium
- Housing colour: traffic white RAL 9016
- Light distribution: direct, narrow distribution
- Type of installation: Track mounting
- Certification mark: IP 20, Protection class I, F, Indoor, CE

## Dimensions



- Dimensions LxWxH/DxH: 75 x 182 (mm)
- External driver housing LxWxH: 205 x 32 x 51 (mm)
- Weight (net): 0.88 (kg)
- Swivel and turn area (x/y/z): + 90° / 0° / 350°

## Lighting/Electrical



- Placement: LED, Colour rendering/Light colour CRI  $\geq 90$  / 4000K
- Direct/Indirect: 100 % / 0 %
- UGR lat/lon: 18.0 / 18.0
- Luminaire luminous flux: 2100 (lm)
- LED service life: 50000h L80/B50 (Tq 25°C)
- Luminaire luminous efficacy: 97 (lm/W)
- System output: 22 (W)
- Controller: Electronic driver (1 pcs.)
- Mains voltage max.: 230 V / 50 Hz